









## RUNWAY SPECIFICATIONS

PVC

2.5mm

7" x 48"

0.5mm | 20 mil

Polyurethane w/

Square Edge

Ceramic Bead, low gloss

Sf Per Carton 41.98 Sf Per Pallet 2,308.9 Installation Glue Down

Classification Better

Residential Warranty 30 Year Limited Wear 10 Year Limited Wear

Commerical Warranty

Cascade XT360

Approved Adhesives

Recommended

Adhesive

Contructions Thickness

Wear Layer

Edge Detail

Size

Finish

Wolf Grip Premium (WLF1000) Armstrong S-995.

## PERFORMANCE TESTING

Dry Static Coefficient Of	ASTM D2047   0.47
Friction	
Wet Static Coefficient Of	ASTM D2047   0.66
Friction	
Critical Radiant Flux	ASTM E648   .588 W / cm <sup>2</sup>
Residual Indentation	ASTM F1914   < 8% Pass
Resistance to Chemicals	ASTM F925   Pass
Resistance to Heat	ASTM F1514   $\Delta E^*$ < 8 Pass
Resistant to Light	ASTM F1515   $\Delta E^*$ < 8 Pass
Squareness	ASTM F2055
	Max Value: ≤0.25mm Pass



